

# CRYSTAL MOUNTAIN

## PRODUCT BROCHURE



**ASPEN**  
POU Water Cooler

# ASPEN

## POU Water Cooler



## PEAK PERFORMANCE AT A VALUE PRICE

The Aspen is the perfect water cooler for the traditional home and office delivery. Featuring Stainless tanks and one-piece blow moulded cabinet, the Aspen is built to perform and backed by the company known for innovation, quality and support.

### Features

- Black and White cabinet options
- Hot & Cold or Cook & Cold models
- #304 stainless cold reservoir
- #304 stainless hot tank
- #304 stainless waterways
- One piece blow moulded polyethylene cabinet
- Internal frame self supporting frame
- ENERGY STAR™ certified



Removable Drip Tray



Carry Handle



# ASPEN

## POU Water Cooler

## Performance and Specifications

### General

Air cooled, POU type water cooler

### Cooler Cabinet

Black or white, one-piece, moulded, polyethylene cabinet

### Faucet Type

Polypropylene (PP) faucet with self closing handle. Hot Faucet includes a Child Resistant Handle which requires dual action to activate

### Cold Water Tank Specifications

Stainless steel #304 or HDPE casing with 3.47L (0.9 gal) volume

Cold water cooling capacity of 2.0L/hr (0.5 gal/hr) based on 21°C (69.8°F) room temperature

### Cold Water Thermostat

Preset at factory to dispense water at temperature from 4-10°C (39.2-50°F)

Adjustable cold control located at the back of the cabinet

### Hot Water Tank Specifications

Stainless steel #304 casing with 2.0L (0.5 gal) volume

Hot water capacity of 4.5L/hr (1.2 gal/hr) based on 21°C (69.8°F) room temperature

### Hot Water Thermostats and Heater

Automatic thermostat control with temperature range of 74-92°C (165.2-197.6°F)

Manual safety reset in case of automatic thermostat failure

450W external mica-heater band

ON/OFF switch is located at the back of the cabinet

Electronic Thermostat System (ETS) is available, which provides for a temperature control range of 88-92°C (190.4-197.6°F)

### Compressor Type

Hermetically sealed reciprocating compressor

220 ~240VAC 50Hz

**Refrigerant Type:** R600a (CFC Free)

**Refrigerant Charge:** 16g (0.56 oz)



## Dimensions and Freight Data

Model	Products Dimensions WxDxH (mm/in.)	Box Dimensions WxDxH (mm/in.)	Product Weight (kg/lb)		Product Boxed Weight (kg/lb)		Loading Qty	
							20FT	40FT
Aspen POU Water Cooler	320x320x980mm	330x330x1000mm	H&C:12.0kg	C&C:11.5kg	H&C:13.0kg	C&C:12.5kg	238 units	504 units
	12.6"x12.6"x38.6"	12.8"x12.8"x39.4"	(25.6 lb)	(25.4 lb)	(28.6 lb)	(27.6 lb)		

*All performances are tested in a controlled environment, certified by a third party. To learn more about these standards, please speak to your Crystal Mountain representative.*



### **Crystal Mountain Products Limited**

#### **European Sales Office**

Fence House, Fence Avenue  
Macclesfield, Cheshire  
United Kingdom SK10 1LT  
Tel: +44(0) 1625 439 111  
Fax: +44 (0) 1625 502 527

E-mail: [cmeurope@crystalcoolers.com](mailto:cmeurope@crystalcoolers.com)

#### **North American Sales Office**

200 Carnegie Drive, Suite 234  
St. Albert, AB, T8N 5A7 Canada  
Toll Free: 800 878 6422  
Tel: 1 780 454 4545

E-mail: [sales@crystalcoolers.com](mailto:sales@crystalcoolers.com)

### **Crystal Mountain Products Inc.**

#### **US Office / Warehouse**

1665 Westbelt Drive  
Columbus, Oh 43228  
Outbound Door #2  
Tel: (614) 454 1618  
Fax: (614) 409 9782

E-mail: [sales@crystalcoolers.com](mailto:sales@crystalcoolers.com)

### **Crystal Mountain International Limited**

#### **Hong Kong Sales Office**

Room 610, Winfield Commercial Building  
6-8a Prat Avenue, Tsimshatsui  
Kowloon, Hong Kong  
Tel: (852) 2368 1989  
Fax: (852) 3017 6727

E-mail: [cmasia@crystalcoolers.com](mailto:cmasia@crystalcoolers.com)



CE  US LISTED CB  SASO ISO9001 WEEE RoHS

**Website: [www.crystalcoolers.com](http://www.crystalcoolers.com)**

Crystal Mountain has a policy of continuous development and reserves the right to change specifications without notification.

