CRYSTAL NOUNTAIN PRODUCT BROCHURE





CRYSTAL PRO POU Water Cooler

CRYSTAL PRO POU Water Cooler

Enjoy purified drinking water that also tastes great with this Crystal Mountain Crystal Pro purified Water dispenser. This product was designed to bring safe drinking water to your facility and fellow associates. Built to work with any filtration system.

Features

- Hot, Ambient and Cold water
- Patented design
- 11.4 litres holding tank (17.8 litres total water storage)
- UV light system at last point before dispense
- UV light failure notification
- Stainless steel hot and cold water reservoirs
- Antimicrobial contact points, drip tray and front panel
- Filter compartment easily removable front access panel
- Auto leak detection with visual and audio alert
- Automatic approach and night lighting
- Illuminated dispense buttons
- Internal RO storage tank
- Electronic/mechanical water level controls
- Integrated Cup Dispenser
- Injection-moulded ABS plastic front panels
- Scratch resistant Metal side panels and self-supporting frame
- UV activation Light visually simulates the sterilization process





Hot, Cold and Ambient water fauce



Removable drip tray



ntegrated cup dispenser



Performance and Specifications

Reverse Osmosis and Filtration options with Ultra Violet sterilization on dispense. High capaity robust cooling and heating systems

Cold Water Tank Specifications

Stainless steel #304 or HDPE casing with 11.4L (3 gal) volume Cold water cooling capacity of 3.5L/hr (0.9 gal/hr) based on 24°C (75.2°F) room temperature **Cold Water Thermostat** Preset at factory to dispense water at temperature from 5-10°C (41-50°F) Adjustable cold control located at the back of the cabinet **Hot Water Tank Specifications** Stainless steel #304 casing with 1.20L (0.5 gal) volume Hot water capacity of 4.5L/hr (1.2 gal/hr)/ based on 24°C (75.2°F) room temperature Hot Water Thermostats and Heater Automatic thermostat control with temperature range of 83°C (181°F) Manual safety reset in case of automatic thermostat failure 450W external mica-heater band ON/OFF switch is located at the back of the cabinet Electronic Thermostat System (ETS) is available, which provides for a temperature control range of 83°C (181°F) **Compressor Type** Hermetically sealed reciprocating compressor 220~240VAC 50Hz Refrigerant Type: R600a

Refrigerant Charge: 20g (0.7 oz)

Dimensions and Freight Data

	Model	Products Dimensions WxDxH (mm/in.)	Box Dimensions WxDxH (mm/in.)	Product Weight (kg/lb)	Product Boxed Weight (kg/lb)	Loading Qty 40FT
	Crystal Pro POU Water Cooler	391x375x1175mm	430x430x1220mm	22.8kg	25.1kg	280 units
		15.4"x14.8"x46.3"	16.9"x16.9"x48"	(51 lb)	(55.3 lb)	

All performances are tested in a controlled environment, certified by a third party. To learn more about these standards, please speak to your Crystal Mountain representative.





Crystal Mountain Products Limited

European Sales Office

Fence House, Fence Avenue Macclesfield, Cheshire United Kingdom SK10 1LT Tel: +44(0) 1625 439 111 Fax: +44 (0) 1625 502 527 E-mail: cmeurope@crystalcoolers.com

North American Sales Office

200 Carnegie Drive, Suite 234 St. Albert, AB, T8N 5A7 Canada Toll Free: 800 878 6422 Tel: 1 780 454 4545 E-mail: sales@crystalcoolers.com

Crystal Mountain Products Inc.

US Office / Warehouse 1665 Westbelt Drive Columbus, Oh 43228 Outbound Door #2 Tel: (614) 454 1618 Fax:(614) 409 9782 E-mail: sales@crystalcoolers.com

Crystal Mountain International Limited

Hong Kong Sales Office

Room 610, Winfield Commercial Building 6-8a Prat Avenue, Tsimshatsui Kowloon, Hong Kong Tel: (852) 2368 1989 Fax: (852) 3017 6727 E-mail: cmasia@crystalcoolers.com











CE C US LISTED CB C SASO ISO9001 WEEE ROHS

Website: www.crystalcoolers.com

Crystal Mountain has a policy of continuous development and reserves the right to change specifications without notification.

