# CRYSTAL NOUNTAIN PRODUCT BROCHURE





**EVEREST ELITE** POU Water Cooler

### **EVEREST ELITE** POU Water Cooler

Inspired by the award winning Everest model, Crystal Mountain introduces the stunning Everest Elite. Innovative design features include: removable side panels, double mechanical float, and raised faucet handles. Its sleek design and upscale look is perfect for either home or office environments. Crystal Mountain proves that anything is possible when there is a drive to reach new heights!





Point of Use Dispenser



Sturdy Metal Faucet Handles



Removable Reservoir/Faucet Assembly (patent pending)

#### Features

- Modern, sleek and stylish design
- Ergonomic faucet height
- Removable Reservoir/faucet assembly
- Easily removable ABS side panels
- Maintenance friendly
- Integrated spring loaded cup dispenser (250 ml flat bottom)

#### Point of Use system

Features a primary float with a secondary backup in conjunction with a 1/4" quick connect fitting with cover to protect the fitting and tubing. Easily adaptable, the double mechanical float system installs easily onto the coolers.







#### **Performance and Specifications**

#### General

An air-cooled water dispenser with a compressor-driven refrigeration system and a removable reservoir for sanitizing

Available in hot and cold, and cold and ambient

#### **Cooler Cabinet**

Plastic outer panels use high gloss ABS, with a chrome strip edging Standard colour - black with chrome accent Other colours may be available in high volume orders **Faucet Type** Mechanically operated self closing faucet made of food grade approved plastics (polypropylene and silicone) Childproof safety faucet handle and button. LED Nightlight **Cold Water Tank Specifications** Polypropylene (PP) casing with 2.4 L (0.6 gal) volume Cold water cooling capacity of 1.5 L/hr (0.4 gal/hr) based on 21°C (69.8°F) room temperature **Cold Water Thermostat** Preset at factory to dispense water at temperatures from 4-10°C (39.2 - 50°F) Adjustable cold control located at back of cabinet **Hot Water Tank** Stainless steel #304 casing with 1.1 L (0.3 gal) volume Hot water capacity of 5.0 L/hr (1.3 gal/hr) based on 21°C (69.8°F) room temperature New: Sealed Bi-Metal (Auto Cutout) Hot Water Thermostat and Heaters Automatic thermostat set at temperature range of 74-92°C (165.2-197.6°F) Manual thermostat reset in case of automatic thermostat failure ON/OFF switch is located at back of cabinet New: Silicone Reset Cover Compressor Hermetically sealed reciprocating compressor (220-240VAC 50Hz) Refrigerant Type: R600a



#### **Dimensions and Freight Data**

Refrigerant Charge: 13g (0.45oz)

| Model  | Products Dimensions<br>WxDxH (mm/in.) | Box Dimensions<br>WxDxH (mm/in.) | Product Weight<br>(kg/lb) | Product Boxed<br>Weight (kg/lb) | Loading Qty |           |
|--|---------------------------------------|----------------------------------|---------------------------|---------------------------------|-------------|-----------|
|  |                                       |                                  | Hot & Cold                | Hot & Cold                      | 20FT        | 40FT      |
| Everest Elite<br>POU water cooler<br>without cup dispenser | 358.5x342x1058mm                      | 290x285x1080mm                   | 12.7 kg                   | 14.0 kg                         | 320 units   | 640 units |
|  | 14.1"x13.5"x41.7"                     | 11.4"x11.2"x42.6"                | 28.0 lb                   | 30.9 lb                         |             |           |
| Everest Elite<br>POU water cooler<br>with cup dispenser    | 358.5x348x1058mm                      | 290x285x1080mm                   | 13.1 kg                   | 14.4 kg                         | 320 units   | 640 units |
|  | 14.1"x13.7"x41.7"                     | 11.4"x11.2"x42.6"                | 28.9 lb                   | 31.8 lb                         |             |           |

All performances are tested in a controlled environment, certified by a third party. To learn more about these standards, please speak to your Crystal Mountain representative.



#### **Crystal Mountain Products Limited**

#### European Sales Office

Fence House, Fence Avenue Macclesfield, Cheshire United Kingdom SK10 1LT Tel: +44(0) 1625 439 111 Fax: +44 (0) 1625 502 527 E-mail: cmeurope@crystalcoolers.com

#### North American Sales Office

200 Carnegie Drive, Suite 234 St. Albert, AB, T8N 5A7 Canada Toll Free: 800 878 6422 Tel: 1 780 454 4545 E-mail: sales@crystalcoolers.com

#### Crystal Mountain Products Inc.

US Office / Warehouse 1665 Westbelt Drive Columbus, Oh 43228 Outbound Door #2 Tel: (614) 454 1618 Fax:(614) 409 9782 E-mail: sales@crystalcoolers.com

#### **Crystal Mountain International Limited**

#### Hong Kong Sales Office Room 610, Winfield Commercial Building

6-8a Prat Avenue, Tsimshatsui Kowloon, Hong Kong Tel: (852) 2368 1989 Fax: (852) 3017 6727 E-mail: cmasia@crystalcoolers.com



## CE CUUSLISTED CB C SASO ISO9001 WEEE ROHS

#### Website: www.crystalcoolers.com

Crystal Mountain has a policy of continuous development and reserves the right to change specifications without notification.

